



# Vista Protos VCMH/VSCMH Housing Range



## Cable managed, stylish housings

The Vista VCMH/VSCMH Housing Range have been designed not only to look good, but are as easy to install, use and service.

Rated to IP66 they all feature a 'slide and hang' servicing facility which allows the top of the housing, when unsecured, to slide forward and hang below the housing body giving the installer maximum accessibility to the camera inside.

Also available are flat sided housings which allows for installer labelling.

- IP65 rated
- 'Slide and hang' service feature
- Heater and thermostat
- Lightweight aluminum housing (weighs just 5kg)
- Available in 240Vac or 24Vac versions

### Ideal for:

Applications such as:

- Town Centres
- Petrol Forecourts
- Car Parks





# VCMH/VSCMH Housing Range

## TECHNICAL SPECIFICATION

### Weatherproof housing

Suitable for use with most CCD camera and lens combinations there are 2 types of housing with different internal dimensions. 'Engineered for the engineer' the housings' design allows for easy installation and servicing without having to remove the main body. Protection rated to IP66 they are solidly manufactured from aluminium.

### Sunshield

Also manufactured in aluminium, the housings feature a 'slide and hang' facility which enables them to be fully opened without removing the sunshield. This gives easy and full access to the camera and lens inside, enabling final adjustments, such as focusing, and any subsequent servicing.

### Paint and finish

The paint finish (colour RAL7035) is an oven sealed epoxy polyester powder which has been specially treated to give a high resistance to atmospheric and conductory agents so these housings look better for longer and are also tolerant to temperatures between -25°C and +200°C.

### Heater

The heating system comprises of a terminal board with thermostat (on @ 10°C, off @ 25°C), protected resistor (2k5 ~ 30W), fixed on a diffuser and fastening screws. The 24Vac option is subject to availability.

### Bracket & Joint - VSCMH

The openings at the base of the bracket are designed for the camera cables to pass through giving a neat installation. The clever design of the joint enables the housing to be installed in any number of different positions and also has the effect of lengthening or shortening the bracket.

### Weatherproof cable cover - VCMH

The VCMH offers totally discrete cable management so none of the cables used are visible. Incorporating both bracket and joint this cable cover creates a continuous cavity simplifying installation and enabling the camera housing to be tilted to any angle. The cable can either be installed from the bottom of the bracket or from the two sides using the two removable plates, with knockouts to use with electrical accessories.



'Slide and hang' facility



VCMH and VCMH 250

### Internal Dimensions (L x W x H)

VCMH/VSCMH/F Ranges: 315 x 105 x 86

VCMH250/VSCMH250 Ranges: 250 x 75 x 70

## ORDERING INFORMATION

VCMH	Fully cable managed housing with integral bracket, heater and thermostat
VSCMH	Semi cable managed housing with integral bracket, heater and thermostat
VCMHF	Flat sided fully cable managed housing with integral bracket, heater and thermostat
VCMHF24	As above, but 24Vac option
VSCMHF	Flat sided semi cable managed housing with integral bracket, heater and thermostat
VSCMHF24	As above, but 24Vac option
VCMH250	Fully cable managed housing with integral bracket, heater and thermostat
VSCM250	Semi cable managed housing with integral bracket, heater and thermostat
V24H	24V heater assembly



Norbain SD Ltd  
Norbain House, Eskdale Road,  
Winnersh Triangle, Wokingham,  
Berkshire RG41 5TS, England.  
Telephone: +44 (0) 118 944 0123  
Facsimile: +44 (0) 118 944 0999  
WebSite: <http://www.vista-cctv.com>

Distributed by:

ALLSPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE